



LD-90 GAS LEAK DETECTOR

LD-90 is a water-based non-flammable professional-grade gas leak detector formulated without solvents, silicones or oils which quickly and safely identifies gas and air leaks in pipework, valves and other fittings. LD-90 highlights nonvisible leaks even on low-pressure systems. Use to trace leaks for all types of gases, forms highly visible bubbles. Suitable for use by heating engineers to check that gas pipes are sealed and there are no appearances of leaks. Conforms to BS EN 14291:2004 (VOSA MOT Testing) and MIL-L-25567 (oxygen system compatibility).

KEY FEATURES

- Economical detector suitable for all types of gases (including oxygen systems)
- Highlights leaks even on low-pressure systems
- Non-flammable, water-based formula
- Conforms to BS EN 14291:2004 (VOSA MOT Testing) and MIL-L-25567 (oxygen system compatibility)
- Does not contain solvents, silicone or oils

MARKET SECTORS:

ENGINEERING
TRADE/PRO-DIY

AC CODE	CRC CODE	SIZE
1930	33173	500ml Aerosol

NEVER ASK A PROFESSIONAL TO USE ANYTHING ELSE!

APPLICATION AREAS

LD-90 is the perfect gas leak detection tool for multiple industries: gas fitting, plumbing, heating, automotive air conditioning, engineering and welding, HVAC, QC tests, maintenance and safety checks on pipework, air lines, joints, valves, cylinders, regulators, air brakes and inflatable equipment.

DIRECTIONS FOR USE

- Ensure that electrical equipment is turned off before testing.
- Spray LD-90 evenly over the area to be tested.
- Bubbles will appear at the location of any leaks.
- Product residues should not be allowed to build up when using on oxygen systems, wash with water after testing.

APPEARANCE:	Clear, colourless liquid
ODOUR:	Odourless
SPECIFIC GRAVITY AT 20°C:	1.00
PH:	8.5
SURFACE TENSION:	28 mN/M
SOLUBILITY:	Soluble in water, insoluble in solvents.
FOAM STABILITY (DIN 53902):	90%
CORROSION TEST (DIN 30657):	Not corrosive

(All values apply to product without aerosol propellant)

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from <https://www.actioncan.com/product/ld-90/> or from info.uk@crcind.com

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.

