

TECHNICAL DATA



LM-90 LINE MARKING PAINT

LM-90 is a permanent, durable line and marking paint for indoor and outdoor surfaces. Quick drying time with a precise flat matt one-coat finish. A spray-on line marking paint that can be applied easily by hand, or using all popular application machines. Use on a multitude of sites including: civil engineering, construction, warehouse, car parks/pavements, and utilities. Suitable for producing highly visible lines and markings with a good adhesion to concrete, stone, tarmac, grass, gravel, and even soil.

A range of popular colours: Orange, Green, Blue, White, Red, Yellow and Black.

COLOUR REFERENCES

YELLOW	RAL 1018	Access aisles
WHITE	RAL 9003	Production Equipment
RED	RAL 1891	Defect/Scrat Areas
BLUE	RAL 5015	Work in Progress
GREEN	RAL 6018	Safety Related Areas
ORANGE	RAL 2003	Machinery parts areas
BLACK	RAL 9004	Finished Goods Areas

KEY FEATURES

- A quick-drying, highly durable, line marking paint
- Fits all popular application machines: easy to apply
- Multi-use paint suitable for: civil engineering, construction, warehouse, car parks/pavements, and utilities
- A range of popular bright colours: Orange, Green, Blue, White, Red, Yellow and Black

MARKET SECTORS:

AGRICULTURE TRADE/PRO-DIY

AC CODE	CRC CODE	SIZE
1744	32824	750ml Aerosol Yellow [RAL 1018]
1745	32825	750ml Aerosol White [RAL 9003]
1891	32826	750ml Aerosol Red [RAL 1819]
1892	32827	750ml Aerosol Blue [RAL 5015]
1893	32828	750ml Aerosol Green [RAL 6018]
1897	32829	750ml Aerosol Orange [RAL 2003]
1898	38230	750ml Aerosol Black [RAL 9004]

NEVER ASK A PROFESSIONAL TO USE ANYTHING ELSE!

APPLICATION AREAS

Suitable for use on concrete, asphalt, wood, and grass/soil for the identification of gas, water and electrical supplies.

DIRECTIONS FOR USE

- Shake the can in order to free the agitator ball, shake for a further minute before use.
- Invert the can and apply onto the surface to be marked.
- Speed of movement during application controls the density of the marking.
- After use, hold the can upright and spray a short burst in order to clear the nozzle.
- Store the can on its side to prevent valve blocking.



TECHNICAL DATA

APPEARANCE:	Matt finish coloured paint
ODOUR:	Solvent
TOUCH DRY:	10 minutes
FULLY CURED:	24 hours
SOLUBILITY:	Insoluble in water, soluble in some solvents
COVERAGE:	1.5mph Walking Pace = 140m line 2.5mph Walking Pace = 220m line

(All values apply to product without aerosol propellant)

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from https://www.actioncan.com/product/lm-90/ or from info.uk@crcind.com

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 1 year with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.



