



AC-90 MULTI-PURPOSE LUBRICANT

AC-90 is a true multi-purpose lubricant for maintenance and engineering professionals requiring a single-can, quick fix solution to common problems. AC-90's unique formulation is based upon decades of real-world performance experience – becoming a trusted and favoured product choice for engineers around the world.

AC-90 Displaces Moisture: AC-90 contains active ingredients which rapidly displace moisture and eliminate damp induced faults on ignition circuits.

AC-90 Lubricates: AC-90 keeps moving parts working smoothly and efficiently, eliminating stick-slip and improving operational efficiency. Does not contain silicone.

AC-90 Penetrates & Releases: AC-90 rapidly penetrates and releases seized, corroded and over-tightened fasteners, leaving a fine lubricating film for ease of reassembly and future protection.

AC-90 Protects Against Rust: AC-90 provides excellent corrosion protection of metal parts and components, repelling atmospheric moisture and inhibiting flash-rusting.

AC-90 Cleans: AC-90 removes heavy oils, light greases, and grime, leaves an anti-stick oily residue after wiping.

KEY FEATURES

- Displaces moisture and eliminates damp induced faults
- Lubricates moving parts to keep them working smoothly and efficiently
- Rapidly penetrates and releases seized parts and fasteners
- Excellent short-term corrosion protection
- Removes heavy oils, light greases, and grime, leaves an anti-stick oily residue after wiping
- Does not contain silicone

MARKET SECTORS

- ENGINEERING
- FASTENERS & FIXINGS
- ELECTRICAL MRO
- AGRICULTURE
- TRADE/PRO-DIY

CODE	REF.	SIZE
1032504	33179	500ml TwinSpray LPG
1031888	32769	425ml Aerosol LPG
1031881	32766	500ml Aerosol LPG
1031886	32768	250ml Aerosol CO ₂
1031884	32767	500ml Aerosol CO ₂
1032455	33156	5L Pack + Trigger Spray
1032007	32852	5L Can
1032008	32853	25L Drum

APPLICATION AREAS

Quick fix instant solution for professional engineers. Lubricates practically everything such as fittings, locks, tools and sliding metal-to-metal parts. Releases rusted threaded fasteners. Cleans industrial equipment and tools.

DIRECTIONS FOR USE

- De-energise equipment, ensure good ventilation, and use appropriate PPE.
- Shake can well for a few seconds.
- Apply to surface from a distance of 25 cm.
- Allow at least 10 minutes for solvent to dissipate before re-energising equipment.

IN THE RIGHT HANDS, IT'S A POWER TOOL!

APPEARANCE:	Pale yellow liquid oil
ODOUR:	Traditional engineering oil
SPECIFIC GRAVITY AT 20°C:	0.837
SOLUBILITY:	Insoluble in water
FLASH POINT:	41°C
ELECTRICAL CONDUCTIVITY:	Non-conductive
FLASH POINT:	>250 °C

(All values apply to product without aerosol propellant)

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from: actioncan.com/product/ac-90/ or from info.uk@crcind.com

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.

