



## BD-90 BELT DRESSING

BD-90 is a belt dressing that improves performance on all types of belts used in industry. It quickly restores grip, prevents slippage, increases pulling power and extends the life of the belt.

BD-90 prevents the belt drying out, hardening or glazing and stops belt squeaks. Exhibits excellent adhesion to the belt surface, preventing fling-off. Ideal for use on belts in humid or outdoor environments: protects against oxidation and moisture.

### KEY FEATURES

- Rapidly restores grip to all types of belts
- Eliminates belt squeak
- Reduces belt slippage and increases pulling power
- Ideal for use on belts in humid or outdoor environments
- Inhibits hardening and glazing of the belt

### MARKET SECTORS:

**AGRICULTURE**  
**INDUSTRIAL MRO**  
**TRADE/PRO-DIY**

CODE	FILL SIZE/PRODUCT
1658	500ml aerosol

## NEVER ASK A PROFESSIONAL TO USE ANYTHING ELSE!

### APPLICATION AREAS

BD-90 can be used on all types of flat, round or v-belts made from rubber, leather, plastic or fabric found on a wide range of machinery including conveyors, compressors, pumps, generators and lift trucks.

### DIRECTIONS FOR USE

- Turn off machinery and ensure that belts are stationary.
- Shake the can well and spray a light even coating from 15 to 20 cm onto the pulling sides of the belt.
- Allow the solvent to evaporate away before re-starting the equipment.
- Re-apply periodically in order to ensure continued performance.
- BD-90 can be removed if necessary with solvent based cleaner such as TF-90 / Partcode 1848. Check for materials compatibility.

APPEARANCE:	Clear, colourless liquid.
ODOUR:	Characteristic solvent.
SPECIFIC GRAVITY AT 20°C:	0.75
VISCOSITY AT 100 °C:	4100 mPa.s
TEMPERATURE RANGE:	-10°C to 100°C
SOLUBILITY:	Insoluble in water

(All values apply to product without aerosol propellant)

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from <https://www.actioncan.com/product/bd-90/> or from [info@actioncan.com](mailto:info@actioncan.com)

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

## TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.

