



SL-90 SYNTHETIC LUBRICATING OIL WITH PTFE

SL-90 is a synthetic oil lubricant developed to provide excellent temperature and pressure resistance. The addition of P.T.F.E. further reinforces the oil film and extends the relubrication interval for metal to metal contact. Upon application, SL-90 penetrates rapidly then thickens to form a tough, high-performance film which has high resistance to wear and creates an effective barrier against salt water, acids and alkalis. The innovative blend of corrosion inhibitors present in SL-90 provides highly durable protection on all types of metal. SL-90 is resistant to temperatures of between -35 and 200 °C.

KEY FEATURES

- Fully-synthetic multi-purpose lubricating oil with exceptional performance
- Multi-viscosity capability with good anti-filing properties
- Wide operating temperature range -35°C to +200°C
- Resistant to water, steam, acid and alkalis
- EP additives improve high load-carrying capacity

MARKET SECTORS:

INDUSTRIAL MRO
FASTENERS & FIXINGS
ELECTRICAL MRO
AGRICULTURE
TRADE/PRO-DIY

CODE	FILL SIZE/PRODUCT
1948	500ml aerosol

NEVER ASK A PROFESSIONAL TO USE ANYTHING ELSE!

APPLICATION AREAS

Use on manual handling equipment: forklifts, chains, jacks and pallet trucks; logistics and warehousing applications: guide rails, conveyors; on agricultural equipment; power transfer components: gears with high point-of-contact temperatures, open gears, and sealed bearings and as a high-performance multi-purpose lubricating oil.

DIRECTIONS FOR USE

- Shake the can before use.
- Spray onto parts requiring lubrication from 15 – 20 cm.

APPEARANCE:	Clear colourless oil
ODOUR:	Minimal
SPECIFIC GRAVITY AT 20°C:	0.84
TEMPERATURE RANGE:	-35°C to 200°C
KINEMATIC VISCOSITY AT 40°C:	20 cSt
SOLUBILITY:	Insoluble in water
BASE OIL(S):	Synthetic
EP ADDITIVE(S):	PTFE

(All values apply to product without aerosol propellant)

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from <https://www.actioncan.com/product/si-90/> or from info@actioncan.com

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.

