



## MP-90 MOISTURE GUARD

MP-90 is a waxy, translucent green, anti-corrosion coating for the long-term (covered) protection of steel. Protects metal components exposed to high humidity conditions. For use indoors and outdoors to displace condensation and moisture, preventing the occurrence of corrosion, rusting and oxidation. Apply the coating to steel components for protection while in storage and international transportation. Ideal for injection moulds and extrusion dies.

### KEY FEATURES

- A flexible, waxy anti-corrosion coating for steel
- Displaces moisture, prevents corrosion, rusting and oxidation
- Light green tracer dye for visual inspection of coverage
- Uniform spray forms a continuous film for complete coverage
- Provides long-term internal and (covered) outdoor protection for stored equipment
- Does not contain silicone

### MARKET SECTORS:

**ENGINEERING**  
**FASTENERS & FIXINGS**  
**TRADE/PRO-DIY**  
**AGRICULTURE**

AC CODE	CRC CODE	SIZE
32802	1980	500ml Aerosol

## NEVER ASK A PROFESSIONAL TO USE ANYTHING ELSE!

### APPLICATION AREAS

Metal components in high humidity conditions requiring protection from atmospheric moisture, such as injection mould tools and extrusion dies. Apply to steel components as an effective international transportation coating.

### DIRECTIONS FOR USE

- Shake the can before use.
- Ensure compatibility on small areas of painted or coated surfaces before general application.
- Spray a light, even coating from 15 – 20 cm over the component to be protected.
- Do not over apply - a light green hue indicates a suitable film thickness.
- Leave the coating to dry before handling.
- MP-90 can easily be removed with solvent cleaner TF-90 / Partcode 1848.

APPEARANCE:	Pale green, waxy film.
ODOUR:	Characteristic solvent.
SPECIFIC GRAVITY AT 20°C:	0.90
SOLUBILITY:	Insoluble in water
ELECTRICAL CONDUCTIVITY:	Non-conductive.

(All values apply to product without aerosol propellant)

---

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from <https://www.actioncan.com/product/mp-90/> or from [info.uk@crcind.com](mailto:info.uk@crcind.com)

---

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

---

## MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

---

## TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.

